

FLUGG Update

Brian Mercurio
MINOS/NOvA Beam WG Meeting
2013/7/26




Nimpwt Bug



- The bug regarding events with $\text{run} = 0$ and $\text{evtno} = 0$ was found to be two bugs.
 - The event number and run number are lost if the neutrino is produced inside a target volume.
 - An if section of the subroutine Fluscw was not always called when whoever wrote this version of FLUGG thought it would be called.
- The bug in Fluscw also caused Nimpwt to be 0 in about 0.5% of events.
- The proposed solution is to reset the importance weight in the user routine Stuprf.
- This was tested by comparing 500,000 POT of me000z200i before the fix to 500,000 POT after the fix.
- All histograms use energy and weight projected to the NOVA Far Detector.




$\nu_\mu + \nu_\mu\text{-bar}$ when $\text{evtno} = 0$



- 2.55295e-05 events before the fix
- 2.65827e-05 events after the fix




$\nu_\mu + \bar{\nu}_\mu$ when $\text{evtno} > 0$



- 0.00600907 events before the fix
- 0.00605427 events after the fix




$\nu_e + \bar{\nu}_e$ when evtno = 0



- 1.01744e-06 events before the fix
- 8.94306e-07 events after the fix



$\nu_e + \bar{\nu}_e$ when $\text{evtno} > 0$



- 6.79694×10^{-5} events before the fix
- 7.09433×10^{-5} events after the fix



Plans



- The Nimpwt bug fix caused no major changes to the neutrino flux.
 - ν_e or ν_μ
 - $\text{evtno} = 0$ or $\text{evtno} > 0$
- Are we ready to put the evtno bug fix back into FLUGG and commit the changes?